

OVERHEAD STATIC ELIMINATOR IONIZER

Brand: **ZE** | Model: **Z209**

HEATEX



APPLICATION AREAS

ESD sensitive work areas and assembly units.

Plastic and paper industries

IT & Computer industry

Clean rooms.

SPECIFICATIONS

Air Flow : 425 cm/hr

Noise level : 55 dbA at 1m

Supply : 230V AC 50Hz 70 Watts

Ionization Potential : 6-8 KV

Ion balance : -/+ 50 V

Construction : Powder-coated Sheet metal enclosure

Dimensions in mm : L1000 x B170 x H130.

Weight : 7 kgs.

Warranty : One year.

:: System Includes

:: Features

The generation and accumulation of unwanted electrostatic charges, both surface and airborne, poses a serious problem in various industries, work areas & laboratories. For instance, static charges can cause havoc in the electronic assembly shopfloor.

This OVERHEAD unit can be conveniently hung over the work area for a large coverage to neutralise the charges on personnel or on any item entering an ESD sensitive area. This is achieved with a stream of ionized air. "Ion showering" is the only effective method of removing static charges from nonconductive objects and surfaces.

The unique high-efficiency pulse circuitry provides fast discharge with limited air flow. It works on the principle of high-voltage corona discharge to produce the neutralising ions. Ion Balance is maintained irrespective of supply voltage and even if the discharge electrodes are dirty. Balanced output is essential when used in critical ESD sensitive areas.