

Plot No 15/EP, Shakthi Sai Nagar,IDA Mallapur, Hyderabad-500076, Telangana, India (P): +91 40 64540825, (M): +91 9949243757

(E): sales@brighttechnologies.in (W): www.brighttechnologies.in

## **Analog solder pot**

Product Name:	Analog solder pot	
Brand:	HEATEX	
Model:	601	
Category:	DIGITAL SOLDER POTS	



System Includes	Features	Specifications
Control unit with Stianless steel 50/40mm pot Power cord	Temperature is adjustable even during work.  Temperature can be adjusted by just turning a knob  Heating Element: The high capacity insulated heating ceramic elements are exchangeable and mounted on the pot. They are thermally insulated from the external sheet metal housing.  High-temperature specifications with a maximum temperature of 450 °C (when using 50mm x 50mm soldering pot)  Operation: Solder Bath primarily used for tin plating stranded wire braids, connecting leads and cable lugs.	<ul> <li>Input Voltage: 250W, 230V AC ±10% 50Hz</li> <li>Temp Range:150-450°C</li> <li>Temp stability: +/- 10°C</li> <li>Bath Capacity: Upto 1 Kg. approx.</li> <li>Mechanical Dimensions</li> <li>Pot dimensions: 50Dia x</li> <li>40mm Depth Stainless steel Agrade</li> <li>Weight: 300grms.</li> </ul>